

Sold To: PLESA ANAHUAC Y CIAS SA DE CV
 AV VALLE DE LAS ALAMEDAS
 NO 66 0
 TULTITLANMEX 54940
 MEXICO
 551-08-38-570
 Fax: 555-31-01-918

Ship To: PLESA TULTITLAN (LECHERIA)
 AV VALLE DE LAS ALAMEDAS NO.
 66 -O COL. SAN FRANCISCO CHILP
 SPUR: 12-831-94 AND 12-832-94
 LECHERIA MEX 54940
 MEXICO
 956-54-72-800

Customer P.O.	19251	Sales Order	207939.26
Product Group	Merchant Bar Quality	Part Number	5337560024010W0
Grade	NUCOR MULTIGRADE	Lot #	JW1410844851
Size	3/8x6" Flat	Heat #	JW14108448
Product	3/8x6" Flat 20' NUCOR MULTIGRADE	B.L. Number	J1-686457
Description	NUCOR MULTIGRADE	Load Number	J1-287442
Customer Spec		Customer Part #	

I hereby certify that the material described herein has been manufactured in accordance with the specifications and standards listed above and that it satisfies those requirements.

Roll Date: 10/3/2014 Melt Date: 9/28/2014 Qty Shipped LBS: 4,900 Qty Shipped Pcs: 32

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	*V	Cb	Sn
0.14%	0.82%	0.011%	0.027%	0.21%	0.28%	0.20%	0.22%	0.067%	0.0503%	0.001%	0.012%
CE4020	CEA529										
0.38%	0.41%										

CE4020: C. E. CSA G4020, AASHTO M270
 CEA529: A529 CARBON EQUIVALENT

Yield 1: 62,100psi (428MPa)

Tensile 1: 80,000psi (552MPa)

Elongation: 23% in 8"(% in 203.3mm)

Yield 2: 61,600psi (425MPa)

Tensile 2: 79,200psi (546MPa)

Elongation 21% in 8"(% in 203.3mm)

Specification Comments: NUCOR MULTIGRADE MEETS THE REQUIREMENTS OF: ASTM A36/A36M-08, A529/529M-05(2009) GR50(345), A572/572M-07 GR50(345), A709/709M-10 GR36(250) & GR50(345), CSA G40.21-04 GR44W(300W) & GR50W(350W) AASHTO M270/M270M-10 GR36(270) & GR50(345), ASME SA36/SA36M-07

Comments: E-mail: websales@nstexas.com

- All manufacturing processes of the steel, including melting, have been performed in the U.S.A.
- Mercury in any form has not been used in the production or testing of this product.
- Welding or weld repair was not performed on this material.
- This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor Corporation.
- Results reported for ASTM E45 (Inclusion content) and ASTM E381 (Macro-etch) are provided as interpretation of ASTM procedures.

Bhargava R Vantari

Bhargava R Vantari
 Division Metallurgist