

## Mill Certification 6/28/2016

MTR #: J1-344346 8812 Hwy 79 W Jewett, TX 75846 (903) 626-4461 Fax: (903) 626-6290

Sold To:

FORTACERO S A DE C V BLVD PRESIDENTE CARLOS SALINAS DE GORTARI KM 8 8 APODACANL 66600 MEXICO 011-52-81-815-65-20-0 Fax: 011-52-81-815-65-29-0

FORTACERO MONTERREY BLVD CARLOS SALINAS DE GORTARI KM 8 8 APODACANL 66600 MEXICO 956-72-39-526

Customer P.O.	4500137364	Sales Order	237980.6	
Product Group	Merchant Bar Quality	Part Number	2140302548010W0 JW1610421551 JW16104215	
Grade	NUCOR MULTIGRADE	Lot #		
Size	4x3x1/4 Angle	Heat #		
Product	4x3x1/4 Angle 40' NUCOR MULTIGRADE	B.L. Number	J1-742275	
Description	NUCOR MULTIGRADE	Load Number	J1-344346	
Customer Spec		Customer Part #	LINE 60	

I hereby certify that the material described herein has been menufadured in accordance with the specifications and standards listed above and that it satisfies those requirements

Roll Date: 6	2/2/2016	Melt Date: 5/30	0/2016 Qty	Shipped LB:	5: 10,440	Qty Shipped	Pcs: 45				'
C 0.12%	Mn 0.84%	P 0.015%	S 0.025%	Si 0.20%	Cu 0.22%	Ni 0.09%	Cr 0.18%	Mo 0.032%	V 0.0431%	Cb 0.000%	Sn 0.009%
CE4020 0.33%	CEA529 0.37%	-									0.000.0

CE4020: C. E. CSA G4020, AASHTO M270 CEA529: A529 CARBON EQUIVALENT

Yield 1: 57,300psi Yield 2: 57,400psi

Tensile 1: 72,600psi

Tensile 2: 73,100psi

Elongation: 24% in 8"(% in 203.3mm)

Elongation 25% in 8"(% in 203.3mm)

Specification Comments: NUCOR MULTIGRADE MEETS THE REQUIREMENTS OF: ASTM A36/A36M-14; A529/529M-05(2009) GR50(345); A572/572M-07 GR50(345); A709/709M-10 GR36(250) & GR50(345); CSA G40.21-04 GR44W(300W)& GR50W(350W); AASHTO M270/M270M-10 GR36(270) & GR50(345); ASME SA36/SA36M-07; MEETS REPORTING REQUIREMENTS OF EN10204 SEC 3.1

Comments: E-mail: websales@nstexas.com

All manufacturing processes of the steel, including melting, casting & hot rolling, have been performed in U.S.A
Mercury in any form has not been used in the production or testing of this product.
Welding or weld repair was not perfomed on this material.
This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor Corporation.
Results reported for ASTM E45 (Inclusion content) and ASTM E381 (Macró-etch) are provided as interpretation of ASTM procedures.

Bgla R Vantari