



WALWORTH®

Industrial de Válvulas, S.A. de C.V.
Av. de la Industria Lote 16 Fracc. Industrial el Trébol
Tepolztotán, Estado de México C.P. 54600

(NUMERO) NUMBER:

(FECHA) DATE:

V06C5814
13/09/2006

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
OF THE FOLLOWING STANDARS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO
DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS
EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 10737P
(CODIGO)


DESCRIPTION: 8" FIG. 5206 F UT WCB, API TRIM No.8
(DESCRIPCION) CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)
VALVE WITH LOW EMISSION CONTROL

(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)
(FUGITIVAS A 50 PPM'S MAX)
()

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	1125	1125	815	815
PNEUMATIC (PSI) (NEUMATICA)			80	80

()

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROP. MECANICAS)							
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG			
			BODY (CUERPO)	WH60780	A 216 WCB	0.215	0.890	0.034	0.019	0.443	0.020	0.047	0.011	0.023	0.004					74.82	43.06
BONNET COVER (BONETE TAPA)	WH13152	A-216/WCB	0.194	0.866	0.032	0.014	0.435	0.033	0.033	0.021	0.025	0.001					73.22	43.06	26.0	49.0	168
Normalized to 930 OC.. Cooled in air. (Normalizado a 930 OC.. Enfriado en aire.)																					
WEDGE DISK PLUG (DISCO)	WBB1191	-217/CA15	0.131	0.646	0.034	0.018	0.527	0.075	13.037	0.041	0.021	0.001					99.32	70.76	26.0	45.0	287
Normalized to 970.00 OC.. Cooled in air. (Normalizado a 970.00 OC.. Enfriado en aire.)																					

CERTIFIED BY: 
QUALITY ASSURANCE
CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD