Industrial de Válvulas, S.A. de C.V.

Tepotzotián, Edo. de México, 54600.

SERIAL NUMBER:

V02C7466

30 APR 02 DATE:

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

API 6D

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK

API 600

- STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS

API 598

- VALVE INSPECTION AND TESTING

API 599

- METAL PLUG VALVES - FLANGED AND WELDING ENDS

ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES

ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS

MSS-SP61

- PRESSURE TESTING OF STEEL VALVES

PART. No.: 25788P

DESCRIPTION: 6" FIG. 5202 F UT HCB, API TRIN No. 8

SPECIFICATION 83000

CAST STEEL GATE VALVE

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			An_	80

											MECHANICAL TESTS							
		CHEMICAL COMPOSITION (%)											TENS	/IELD	ELG	RED	BHN	
ITEM	HEAT No.	MATERIAL (ASTM)	С	Mn	Р	S	Si	Ni	Cr	Мо	Cu	٧	W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BODY	18244458	A 216 WCB	0.210	0.770	0.009	0.014	0.440	0.040	0.060	0.010	0.040	0.001		70.75	42.67	27.0	56.0	156
BONNET-COVER	RA61	A 216 WCB	0.210	0.860	0.019	0.013	0.410	0.040	0.050	0.020	0.030	0.011		79.00	48.86	33.6	53.6	159
WEDGE-DISC- Plug	3359A167	A 216 WCB	0.200	0.870	0.015	0.015	0.430	0.080	0.120	0.030	0.048	0.001		75.24	48.29	7 27.0	56.0	156
													•					
														:				

Jorge Soto

CERTIFIED BY:

QUALITY ASSURANCE