Industrial de Válvulas, S.A. de C.V.

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

API 6D

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK

API 600

- STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS

API 598

- VALVE INSPECTION AND TESTING

API 599

- METAL PLUG VALVES - FLANGED AND WELDING ENDS

ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES

ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS

MSS-SP61

- PRESSURE TESTING OF STEEL VALVES

PART. No.: 25786P

DESCRIPTION: 4" FIG. 5202 F UT MCB. API TRIN No. 8

CAST STEEL GATE VALVE

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			A0	MA.

														MECHANICAL TESTS						
		CHEMICAL COMPOSITION (%)									TENS	YIELD	ELG	RED	BHN					
ITEM	HEAT No.	MATERIAL (ASTM)	С	Mn	P	S	Si	Ni	Cr	Мо	Cu	V	W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG		
BODY	RC43	A 216 WCB	0.200	0.840	0.023	0.012	0.420	0.080	0.070	0.030	0.050	0.012		79.60	48.5	33.8	54.1	156		
BONNET-COVER	RC51	A 216 WCB	0.210	0.850	0.022	0.013	0.460	0.070	0.090	0.030	0.040	0.013		79.30	48.5	33.8	54.0	159		
WEDGE-DISC- PLUG	PS	A 217 CA15	0.130	0.720	0.024	0.015	1.010	0.530	13.100	0.200				103.50	76.4	18.2	35.3	269		

CERTIFIED BY:

QUALITY ASSURANCE