V02C8604 29 APR 02

DATE:

Industrial de Válvulas, S.A. de C.V.

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

API 6D

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK

API 600

- STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS

API 598

- VALVE INSPECTION AND TESTING

API 599

- METAL PLUG VALVES - FLANGED AND WELDING ENDS

ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES

ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS

MSS-SP61

- PRESSURE TESTING OF STEEL VALVES

PART. No.: 25786P

DESCRIPTION: 4" FIG. 5202 F UT MCB, API TRIN No. 8

CAST STEEL GATE VALVE

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			80	80

													MECHANICAL TESTS					
					CHE	MICAL	COMP	OSITIO	ON (%)					TENS	YIELD	ELG	RED	BHN
ITEM	HEAT No.	MATERIAL (ASTM)	С	Mn	Р	S	SI	Ni	Cr	Мо	Cu	٧	W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BODY	RC45	A 216 WCB	0.200	0.830	0.021	0.012	0.450	0.050	0.070	0.010	0.040	0.012		78.60	48.10	33.4	53.3	152
BONNET-COVER	1 803A 520	A 216 MCB	0.210	0.870	0.018	0.020	0.380	0.080	0.130	0.030	0.042	0.002		71.87	42.67	26.0	56.0	156
NEDGE-DISC- PLUG	Q T	A 217 CA1	0.110	0.750	0.023	0.012	1.080	0.540	13.300	0.210				103.60	76.2	18.4	35.4	277
:																		

CERTIFIED BY:

Jorge Soto **QUALITY ASSURANCE**