SERIAL NUMBER: DATE:

V02C485 30 APR 02

Industrial de Válvulas, S.A. de C.V.

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

API 6D

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK

API 600

- STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS

API 598

- VALVE INSPECTION AND TESTING

API 599

- METAL PLUG VALVES - FLANGED AND WELDING ENDS ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES

ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS

MSS-SP61

- PRESSURE TESTING OF STEEL VALVES

PART. No.: 82607P

DESCRIPTION: 3º FIG. 5275 F UT HCB, API TRIN No. 8

SPECIFICATION 83000

CAST STEEL GLOBE VALVE

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	315	N A
PNEUMATIC (PSI)			80	N.A.

		CHEMICAL COMPOSITION (%)											MECHANICAL TESTS						
												TENS	YIELD	ELG	RED	BHN			
ITEM	HEAT No.	MATERIAL (ASTM)	С	Mn	Р	s	Si	Ni	Cr	Мо	Cu	٧	· W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG	
BODY	2720A012	A 216 WCB	0.190	0.870	0.011	0.009	0.360	0.190	0.140	0.050	0.026	0.001		70.7	5 42.6	7 32.0	61.0	156	
BONNET-COVER	02D75B	A 216 WCB	0.210	0.810	0.015	0.014	0.410	0.080	0.120	0.030	0.039	0.001		75.2	4 46.0	4 31.6	59.0	156	
WEDGE-DISC- PLUG	44-02	A 276 410	0.129	0.913	0.020	0.009	0.665	0.222	12.926	0.031	0.058			92.0	0 75.0	0 35.0	50.0	196	
		,																	

Jorge Soto

CERTIFIED BY:

QUALITY ASSURANCE