



Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,  
Fraccionamiento Industrial El Trébol  
Tepetzotlán, Edo. de México, 54600.

SERIAL NUMBER:

V02G591

DATE:

24 MAY 02

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED  
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE  
OF THE FOLLOWING STANDARS:

- |             |   |
|-------------|---|
| API 6D      | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK      |
| API 600     | - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS |
| API 598     | - VALVE INSPECTION AND TESTING                      |
| API 599     | - METAL PLUG VALVES - FLANGED AND WELDING ENDS      |
| ANSI B16.10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  |
| ANSI B16.34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS      |
| MSS-SP61    | - PRESSURE TESTING OF STEEL VALVES                  |

PART. No.: 82537P

DESCRIPTION: 8" FIG. 5281 F UT WCB, API TRIM No. 8  
CAST STEEL GLOBE VALVE

SPECIFICATION 83000

| PRESSURE TESTS    | SHELL | BACK SEAT | 1ST SIDE | 2ND SIDE |
|-------------------|-------|-----------|----------|----------|
| HYDROSTATIC (PSI) | 1125  | 1125      | 825      | N A      |
| PNEUMATIC (PSI)   |       |           | 80       | N A      |

| ITEM            | HEAT No. | MATERIAL (ASTM) | CHEMICAL COMPOSITION (%) |       |       |       |       |       |       |       |       |       |       | MECHANICAL TESTS |       |      |     |     |
|-----------------|----------|-----------------|--------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------------------|-------|------|-----|-----|
|                 |          |                 | C                        | Mn    | P     | S     | Si    | Ni    | Cr    | Mo    | Cu    | V     | W     | TENS             | YIELD | ELG  | RED | BHN |
|                 |          |                 | KPSI                     | KPSI  | %     | %     | %     | %     | %     | %     | %     | %     | %     | CVN@             | 1ST   | 2ND  | 3RD | AVG |
| BODY            | 3706A013 | A 216 WCB       | 0.200                    | 0.820 | 0.016 | 0.013 | 0.340 | 0.100 | 0.200 | 0.040 | 0.043 | 0.002 | 74.12 | 46.04            | 30.0  | 59.0 | 156 |     |
| BONNET-COVER    | 3707A004 | A 216 WCB       | 0.210                    | 0.940 | 0.015 | 0.011 | 0.420 | 0.070 | 0.120 | 0.030 | 0.033 | 0.002 | 76.36 | 46.04            | 28.0  | 59.0 | 156 |     |
| WEDGE-DISC-PLUG | 1385A007 | A 216 WCB       | 0.190                    | 0.810 | 0.014 | 0.010 | 0.380 | 0.100 | 0.280 | 0.030 | 0.029 | 0.002 | 74.12 | 42.67            | 31.0  | 59.0 | 156 |     |

*George Soto*

CERTIFIED BY:

QUALITY ASSURANCE