



Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,
Fraccionamiento Industrial El Trébol
Tepotztlán, Edo. de México, 54600.

SERIAL NUMBER:

V03C2344

DATE:

28 FEB 03

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
OF THE FOLLOWING STANDARDS:

- | | |
|-------------|---|
| API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 600 | - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS |
| API 598 | - VALVE INSPECTION AND TESTING |
| API 599 | - METAL PLUG VALVES - FLANGED AND WELDING ENDS |
| ANSI B16.10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES |
| ANSI B16.34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES |

PART. No.: 25780P

DESCRIPTION: 2" FIG. 5202 F UT WCB, API TRIM No. 8
VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES
FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			00	00

ITEM	HEAT No.	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)										MECHANICAL TESTS					
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN
			KPSI	KPSI	%	%	CVN@	1ST	2ND	3RD	AVG							
CUERPO	3220	A 216 WCB	0.210	0.990	0.030	0.020	0.490	0.037	0.024	0.005	0.033	0.003	79.05	48.58	26.0	48.0	153	
BOMETE-TAPA	3199	A 216 WCB	0.220	0.960	0.028	0.016	0.480	0.044	0.077	0.001	0.059	0.003	75.41	44.96	27.0	52.0	144	
CUNA-DISCO-TAPON	B3955	A 217 CA15	0.120	0.660	0.018	0.014	0.880	0.040	13.400	0.018	0.035	0.002	97.17	70.05	27.0	56.0	282	

CERTIFIED BY:

QUALITY ASSURANCE