



Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,  
Fraccionamiento Industrial El Trébol  
Tepetzotlán, Edo. de México, 54600.

SERIAL NUMBER:

V03C4119  
31 JAN 03

DATE:

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED  
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE  
OF THE FOLLOWING STANDARDS:

- |             |   |
|-------------|---|
| API 6D      | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK      |
| API 600     | - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS |
| API 598     | - VALVE INSPECTION AND TESTING                      |
| API 599     | - METAL PLUG VALVES - FLANGED AND WELDING ENDS      |
| ANSI B16.10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  |
| ANSI B16.34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS      |
| MSS-SP61    | - PRESSURE TESTING OF STEEL VALVES                  |

PART. No.: 25786P

DESCRIPTION: 4" FIG. 5202 F UT WCB, API TRIM No. 8  
VALV. COMP. DE ACERO FUW8.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES  
FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			80	80

ITEM	HEAT No.	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											MECHANICAL TESTS				
			C	Mn	P	S	Si	NI	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN
															KPSI	KPSI	%	%
CUERPO	RGL4	A 216 WCB	0.200	0.820	0.021	0.011	0.480	0.020	0.090	0.010	0.070	0.013	78.50	48.24	30.0	50.3	159	
BONETE-TAPA	1803A746	A 216 WCB	0.190	0.760	0.019	0.012	0.420	0.050	0.100	0.030	0.034	0.002	76.36	46.04	24.0	42.0	156	
CUNA-DISCO-TAPON	B3949	A 217 CA15	0.100	0.890	0.016	0.017	0.950	0.039	12.960	0.018	0.037	0.001	96.89	69.62	27.0	56.0	275	

CERTIFIED BY:

QUALITY ASSURANCE