**WALWORTH®**

*Industrial de Válvulas, S.A. de C.V.*
Av. de la Industria Lote 16 Fracc. Industrial el Trébol
Tepotzotlán, Estado de México C.P. 54600

(NUMERO) **NUMBER:** V03C5950
(FECHA) **DATE:** 30 JUN 03

# QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE
# ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

**WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:**

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

| | |
|---|---|
| API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 600 | - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS |
| API 598 | - VALVE INSPECTION AND TESTING |
| API 599 | - METAL PLUG VALVES - FLANGED AND WELDING ENDS |
| ANSI B16 .10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES |
| ANSI B16 .34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES |

**PART. No.:** (CODIGO) 25780P

**DESCRIPTION:** (DESCRIPCION) 2" FIG. 5202 F UT WCB, API TRIM No. 8 VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX

| PRESSURE TESTS (PRUEBAS DE PRESION) | SHELL (CASCO) | BACK SEAT | SIDE (LADO) 1 | SIDE (LADO) 2 |
|---|---|---|---|---|
| HYDROSTATIC (PSI) (HIDROSTATICA) | 450 | 450 | N A | N A |
| PNEUMATIC (PSI) (NEUMATICA) | | | 80 | 80 |

| ITEM (PARTE) | HEAT No. (COLADA) | MATERIAL (ASTM) | C | Mn | P | S | Si | Ni | Cr | Mo | Cu | V | W | MECHANICAL TESTS (PROP. MECANICAS) TENS KPSI CVN@ | YIELD KPSI 1ST | ELG % 2ND | RED % 3RD | BHN AVG |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA) | | | | | | | | | | | | | | | | |
| CUERPO | 3988 | A 216 WCB | 0.190 | 0.930 | 0.018 | 0.011 | 0.450 | 0.028 | 0.071 | | 0.048 | 0.002 | | 76.14 | 45.68 | 26.0 | 48.0 | 147 |
| BONETE-TAPA | 3985 | A 216 WCB | 0.220 | 0.880 | 0.029 | 0.016 | 0.380 | 0.018 | 0.029 | | 0.034 | 0.004 | | 78.30 | 47.12 | 24.0 | 45.0 | 152 |
| CUNA-DISCO-TAPON | 84388 | A 217 CA15 | 0.100 | 0.920 | 0.016 | 0.018 | 0.870 | 0.041 | 12.840 | 0.017 | 0.037 | 0.001 | | 99.35 | 76.57 | 26.0 | 43.0 | 280 |

**CERTIFIED BY:**
CERTIFICADO POR:
QUALITY ASSURANCE
ASEGURAMIENTO DE CALIDAD

FAC10-21 REV "1"