WALWORTH

Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,
Fraccionamiento Industrial El Trébol
Tepotzotlán, Edo. de México, 54600.

SERIAL NUMBER: V03C742
DATE: 28 FEB 03

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

API 6D	- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
API 600	- STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS
API 598	- VALVE INSPECTION AND TESTING
API 599	- METAL PLUG VALVES - FLANGED AND WELDING ENDS
ANSI B16.10	- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
ANSI B16.34	- VALVES - FLANGED, THREADED, AND WELDING ENDS
MSS-SP61	- PRESSURE TESTING OF STEEL VALVES

PART. No.: 25790P

DESCRIPTION: 8" FIG. 5202 F UT WCB, API TRIM No. 8
VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES
FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	315	315
PNEUMATIC (PSI)			80	80

		CHEMICAL COMPOSITION (%)													MECHANICAL TESTS				
ITEM	HEAT No.	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W		TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
CUERPO	SA92	A 216 WCB	0.180	0.880	0.021	0.015	0.420	0.040	0.090	0.030	0.080	0.010			76.63	354.00	26.8	46.9	156
BONETE-TAPA	RG21	A 216 WCB	0.190	0.870	0.019	0.011	0.410	0.020	0.040	0.010	0.030	0.011			77.69	48.34	33.2	57.6	163
CUNA-DISCO-TAPON	SA81	A 216 WCB	0.200	0.910	0.021	0.012	0.520	0.060	0.090	0.020	0.070	0.011			78.23	55.12	24.2	44.6	159

CERTIFIED BY: _____
QUALITY ASSURANCE

FAC10-21 REV. "1"