



# WALWORTH®

Industrial de Válvulas, S.A. de C.V.  
 Av. de la Industria Lote 16 Fracc. Industrial el Trébol  
 Tepotzotlán, Estado de México C.P. 54600

(NUMERO) NUMBER:

V03R2528 ✓

(FECHA) DATE:

11/12/2003

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED  
 ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE  
 OF THE FOLLOWING STANDARDS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO  
 DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS  
 EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 01419H  
 (CODIGO)

DESCRIPTION: 2" FIG. 5350 F AA WCB, API TRIM No.1  
 (DESCRIPCION) CAST STEEL SWING CHECK VALVE (VALVULA RETENCION TIPO COLUMPIO DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL

(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)  
(FUGITIVAS A 50 PPM'S MAX)

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2225	N A	N A	1630
PNEUMATIC (PSI) (NEUMATICA)			N A	N A

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROP. MECANICAS)									
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG					
BODY (CUERPO)	V3114	A 216 WCB	0.210	1.050	0.022	0.028	0.530	0.090	0.060	0.010	0.030	0.001							77.43	48.72	27.0	45.0	154
BONNET COVER (BONETE TAPA)	S3074	A 105N	0.220	0.660	0.013	0.014	0.320	0.025	0.035	0.002	0.020	0.001							84.10	51.47	24.0	48.0	175
WEDGE DISK PLUG (BISCO)	C3446	217 CA15	0.080	0.770	0.015	0.010	0.790	0.490	12.300	0.270	0.000	0.000							104.40	73.69	27.0	39.0	266

CERTIFIED BY:

  
QUALITY ASSURANCE

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD