



Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,
Fraccionamiento Industrial El Trébol
Tepetzotlán, Edo. de México, 54600.

SERIAL NUMBER:

V03R330
28 FEB 03

DATE:

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
OF THE FOLLOWING STANDARS:

- | | |
|-------------|---|
| API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 600 | - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS |
| API 598 | - VALVE INSPECTION AND TESTING |
| API 599 | - METAL PLUG VALVES - FLANGED AND WELDING ENDS |
| ANSI B16.10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES |
| ANSI B16.34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES |

PART. No.: 75715P

DESCRIPTION: 6" FIG. 5341 F UT WCB, API TRIM No. 8
VALV. RET. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES
FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	N A	N A	315
PNEUMATIC (PSI)			N A	N A

ITEM	HEAT No.	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)										MECHANICAL TESTS					
			C	Mn	P	S	SI	NI	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN
			KPSI	KPSI	%	%												
CUERPO	3124A128	A 216 WCB	0.200	0.870	0.022	0.015	0.440	0.090	0.240	0.070	0.037	0.003	75.24	47.17	28.0	54.0	156	
BONETE-TAPA	3086A071	A 216 WCB	0.210	0.830	0.023	0.014	0.380	0.100	0.250	0.070	0.034	0.003	78.61	46.04	25.0	48.0	156	
CUNA-BISCO-TAPON	2145A080	A 216 WCB	0.210	0.790	0.019	0.011	0.400	0.100	0.110	0.040	0.077	0.002	80.86	48.29	31.0	54.0	163	

CERTIFIED BY:

QUALITY ASSURANCE