



# WALWORTH®

Industrial de Válvulas, S.A. de C.V.  
Av. de la Industria Lote 11 Fracc. Industrial el Trébol  
Tepic, Jalisco, México C.P. 51600

(NUMERO) NUMBER: V04R1445

31/05/2004

(FECHA) DATE:

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 000120  
(CODIGO)

DESCRIPTION: 6" FIG. 5341 F UT WCB, API TRIM No. 3  
(DESCRIPCION) CAST-STEEL SWING CHECK VALVE (VALVULA RETENCION TIPO COLUMPIO DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL

(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)  
(FUGITIVAS A 50 PPM'S MAX)

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	NA	NA	315
PNEUMATIC (PSI) (NEUMATICA)			NA	NA

ITEM (PARTE)	HEAT NO. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROR MECANICAS)					
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS -KPSI- CVN@	YIELD -KRST- 1ST	ELG -%- 2ND	RED -%- 3RD	BHN AVG	
			BODY (CUERPO)	W9892	A 216 WCB	0.210	0.830	0.031	0.031	0.470	0.110	0.060	0.510	0.010	0.001				
BONNET COVER (BONETE TAPA)	W9547	A 216 WCB	0.210	0.820	0.038	0.031	0.420	0.100	0.050	0.520	0.010	0.001							
WEDGE DISK PLUG (DISCO)	C2915	A 216 WCB	0.200	0.840	0.019	0.016	0.460	0.030	0.140	0.502	0.030	0.004							

CERTIFIED BY:

QUALITY ASSURANCE

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD

0102

01 08 03 10:49 FAX