



WALWORTH®

Industrial de Válvulas, S.A. de C.V.
Av. de la Industria Lote 16 Fracc. Industrial el Trébol
Tepozotlán, Estado de México C.P. 54600

(NUMERO) NUMBER:

(FECHA) DATE:

V04R3697
12/11/2004

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
OF THE FOLLOWING STANDARDS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO
DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS
EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART No.: 016185
(CODIGO)

DESCRIPTION: 4" FIG. 5341 F UT WCB, API TRIN No.8
(DESCRIPCION) CAST STEEL SWING CHECK VALVE (VALVULA RETENCION TIPO COLUMPIO DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL

(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)
(FUGITIVAS A 50 PPM'S MAX)

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	N A	N A	315
PNEUMATIC (PSI) (NEUMATICA)			N A	N A

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROP. MECANICAS)									
			C	Mn	P	S	SI	Ni	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN					
			CVN@	1ST	2ND	3RD	AVG																
BODY (CUERPO)	084791	A 216 WCB	0.190	0.850	0.031	0.026	0.480	0.040	0.050	0.060	0.050	0.010							83.37	40.16	27.0	44.0	140
BONNET COVER (BONETE TAPA)	084816	A 216 WCB	0.230	0.840	0.033	0.029	0.470	0.020	0.030	0.020	0.050	0.010							83.95	40.74	29.0	42.0	140
WEDGE DISK PLUG (DISCO)	E4158	A 105W	0.250	0.630	0.016	0.014	0.320	0.180	0.220	0.060	0.170	0.010							83.23	52.92	44.0	63.0	187

CERTIFIED BY:

QUALITY ASSURANCE
ASEGURAMIENTO DE CALIDAD

CERTIFICADO POR: