



VALVULAS WORCESTER DE MEXICO, S.A. DE C.V.

RHINO VALVES WORLDWIDE



**CERTIFICADO DE CALIDAD/QUALITY CERTIFICATE**

EN 10 204 3.1 B

<b>Factura / Invoice:</b>	<b>Cantidad / Quantity:</b>	<b>Certificado / Certificate:</b>	<b>Fecha / Date:</b>
98647	30.00	EE98647/69	30/Ene/04
<b>Descripción / Description:</b>			
444-T 1" S.E. NPT			
<b>Cliente / Customer:</b>			
7 TUBOS CONEXIONES Y TANQUES, S. A. DE C. V.			

**Numeros de Rastreabilidad / Traceability Number:**

**03L04015 A 03L04024,03L04005 A 03L04014,03L03995 A 03L04004**

ORIGINAL

Válvulas Worcester de México, S.A. de C.V., certifica que el material indicado cumple con nuestras especificaciones como se describe en nuestras catálogos, hojas de especificación, dibujos y en otra literatura. Los productos, partes, materiales indicados aquí han sido comprados, fabricados, inspeccionados, probados de acuerdo con estas especificaciones, a nuestro sistema de calidad ISO 9001, y ASME/ANSI B16.34-1998 inciso (7).

Válvulas Worcester de México, S.A. de C.V., hereby certifies that the material supplied is in accordance with our specifications as describe in our catalog, specification sheets, drawings, and other literature. The products, parts and materials identified herein have been purchased, manufactured, inspected and tested in accordance with these specifications, our ISO 9001 quality assurance program, and ASME/ANSI B16.34-1998 part (7).


Elaboro / Elaborated by:   
 Jose Luis Perez C.  
 Metrologista

Aprobo / Aprobed by:   
 Ing. Saturnino Padilla Becerra.  
 Gerente de Aseguramiento de Calidad  
 Quality Ass. Manager.

Maiz No. 263, Colonia Valle del Sur, Delegación Iztapalapa, México D.F. C.P. 09819

Teléfonos: 56-70-51-55 (8 líneas) 56-70-66-24 55-82-91-03 5582-30

Fax: 56-70-67-41 56-70-35-13 e-mail: calidadw@worcester.com.mx



VALVULAS WORCESTER DE MEXICO, S.A. DE C.V.  
RHINO VALVES WORLDWIDE



CERTIFICADO DE CALIDAD / QUALITY CERTIFICATE

CERTIFICADO / CERTIFICATE:

EE98647/69

No.	COMPONENTES	MATERIAL
1	CUERPO / BODY	ASTM A216 WCB
2	TAPA / PIPE END	ASTM A216 WCB
3	VASTAGO / STEM	AISI 12L 14
4	ESFERA / SPHERE	ASTM A351 CF8M

No.	C%	Mn%	Si%	P%	S%	Cr%	Mo%	Ni%	Cu%	V%	Fe%	Al%	N%	Zn%	Pb%	Sn%	PROPIEDADES MECANICAS / MECHANICAL PROPERTIES					
																	RESISTENCIA A LA TENSION TENSILE STRENGTH	LIMITE DE CEDENCIA YIELD STRENGTH	% ELONGACION % ELONGATION	REDUCCION DE AREA REDUCTION AREA	DUREZA HARDNESS	
1	0.220	0.890	0.440	0.019	0.007	0.023	0.014	0.018	0.044	0.012	X	X	X	X	X	X	X	545 Mpa	320 Mpa	27	47	157 HB
2	0.180	0.870	0.380	0.016	0.008	0.137	0.001	0.001	0.032	0.021	X	X	X	X	X	X	X	555 Mpa	335 Mpa	27	46	159 HB
3	0.070	1.140	0.010	0.051	0.260	0.060	0.015	0.060	0.110	X	X	0.001	X	X	X	X	X	X	X	43	X	180 BHN
4	0.044	0.617	0.550	0.025	0.008	18.735	2.135	10.221	X	X	X	X	X	X	X	X	X	60.55 Kg/mm <sup>2</sup>	32.21 Kg/mm <sup>2</sup>	43	X	152.72 HB

**ORIGINAL**

TIPO DE PRUEBA TYPE OF TEST	PSI	RESULTADO RESULT
PRUEBA HIDRAULICA DEL CUERPO HYDRAULIC TEST ON BODY	1500	SIN FUGA "OK" NO LEAKAGE FOUND
PRUEBA HIDRAULICA EN ASIENTOS HYDRAULIC TEST ON SEATS	1100	SIN FUGA "OK" NO LEAKAGE FOUND
PRUEBA NEUMATICA EN ASIENTOS NEUMATIC TEST ON SEATS	50-80	SIN FUGA "OK" NO LEAKAGE FOUND